

EVINRUDE® E-TEC® KICKER

15 H.O.



SPECIFICATIONS

Engine Type	Inline 2-Cylinder E-TEC D.I.
Bore x Stroke - in (mm)	2.992 x 2.5 (76 x 64)
Displacement - cu in (cc)	35 (575)
Gear Ratio	2.15:1
Full Throttle RPM Range	5000-5500 RPM
Starting	Electric and Rope
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	56 Amps Total / 15 Amps Net Dedicated
Trim Method	High Speed Power Tilt
Trim Range	-6° to 15°
Tilt Range	75°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - qt (L)	1.7 (1.6)
Recommended Oil	XPS Marine XD100 / XD50
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union

COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)
Graphite	20 (508)	Tiller (Remote avail.)	E15HTGL	187 (85)
		Remote (Tiller avail.)	E15HPGL	181 (82)
White	25 (635)	Remote (Tiller avail.)	E15HPGX	184 (84)
		Tiller (Remote avail.)	E15HTSL	187 (85)
		Remote (Tiller avail.)	E15HPSL	181 (82)
	25 (635)	Remote (Tiller avail.)	E15HPSX	184 (84)

* Variable Voltage Computer Controlled 56 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 15 Amp. Specifications subject to change.
 ©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.