

EVINRUDE® E-TEC®

# 25 HP



## SPECIFICATIONS

<b>Engine Type</b>	Inline 2-Cylinder E-TEC D.I.
<b>Bore x Stroke - in (mm)</b>	2.992 x 2.5 (76 x 64)
<b>Displacement - cu in (cc)</b>	35 (575)
<b>Gear Ratio</b>	2.15:1
<b>Full Throttle RPM Range</b>	5500-6000 RPM
<b>Controls</b>	Mechanical
<b>Fuel Induction</b>	E-TEC Direct Injection with stratified low RPM combustion mode
<b>Alternator Output*</b>	56 Amps Total / 15 Amps Net Dedicated
<b>Trim Range</b>	-4° to 16°
<b>Tilt Range</b>	65°
<b>Lubrication</b>	Multi-Point Targeted Oiling
<b>Oil Tank Capacity - qt (L)</b>	1.7 (1.6)
<b>Recommended Oil</b>	XPS Marine XD100 / XD50
<b>Recommended Fuel</b>	87 Octane
<b>Warranty</b>	3-Year, Non-Declining
<b>100% Global Emissions Compliant</b>	EPA 2013 / CARB 3 STAR / European Union

COLOR	SHAFT LENGTH - in. (mm)	STEERING	STARTING	TRIM METHOD	MODEL NO.	WEIGHT - lb (kg)
Graphite	15 (381)	Tiller (Remote avail.)	Rope (Electric acc.)	Manual Tilt	E25DRG	150 (68)
			Electric & Rope	Manual Tilt	E25DGTE	162 (74)
			Rope (Electric acc.)	Manual Tilt	E25DRGL	154 (70)
	20 (508)	Tiller (Remote avail.)	Electric & Rope	Manual Tilt	E25GTEL	166 (75)
			Electric & Rope	Power Trim & Tilt	E25DGTL	187 (85)
			Electric & Rope	Power Trim & Tilt	E25DPGL	181 (82)
White	15 (381)	Tiller (Remote avail.)	Rope (Electric acc.)	Manual Tilt	E25DRS	150 (68)
			Rope (Electric acc.)	Manual Tilt	E25DRSL	154 (70)
			Electric & Rope	Power Trim & Tilt	E25DTSL	187 (85)
	20 (508)	Tiller (Remote avail.)	Electric & Rope	Power Trim & Tilt	E25DPSL	181 (82)
			Electric & Rope	Power Trim & Tilt	E25DPSL	181 (82)
			Electric & Rope	Power Trim & Tilt	E25DPSL	181 (82)

\* Variable Voltage Computer Controlled 56 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 15 Amp. Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

**EVINRUDE**