

EVINRUDE® E-TEC®

# 90 HP

## SPECIFICATIONS

Engine Type	Inline 3-Cylinder E-TEC D.I.
Bore x Stroke - in (mm)	3.62 x 2.60 (92 x 66)
Displacement - cu in (cc)	79 (1.29)
Gear Ratio	2.00:1
Full Throttle RPM Range	5000-5500 RPM
Starting	Electric
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	81 Amps Total / 25 Net Dedicated
Steering	Remote (Tiller accessory)
Trim Method	Trac-1 Power Trim and Tilt
Trim Range	-4° to 17°
Tilt Range	75°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - qt (L)	3 (2.8)
Recommended Oil	XPS Marine XD100 / XD50
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



COLOR	SHAFT LENGTH - in. (mm)	GEAR RATIO	MODEL NO.	WEIGHT - lb (kg)
Graphite	20 (508)	2.00:1	E90DPGL	320 (145)
	25 (635)	2.25:1	E90DGX	335 (152)
White	20 (508)	2.00:1	E90DSL	320 (145)
	25 (635)	2.25:1	E90DPX	335 (152)

\* Variable Voltage Computer Controlled 81 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp. Specifications subject to change.  
©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

**EVINRUDE**