



Bombardier Recreational Products Inc.
10101 Science Drive
Sturtevant, WI 53177
www.evinrude.com



Avalon & Tahoe Mfg
903 Michigan Avenue
Alma, MI 48801
1-989-463-2112
www.avalonpontoons.com



2014 Avalon LS 1900

BOAT	
2014 Avalon LS 1900	
Material:	Aluminum
Length:	19'
Beam:	8' 6"
Weight w/o Engine:	1650 Lbs
Maximum HP:	60 HP
Fuel Capacity:	32 Gallon
Transom Height:	20"
Steering:	Cable

ENGINE	
Evinrude® 40 HP ETEC®	
Engine Type:	In Line 2 Cyl
Horsepower:	40 HP @ 5750 RPM
Displacement:	52.7 Cu In
Induction:	ETEC DFI
Operating Range:	5500-6000 RPM
Weight:	232 LBS Dry Weight
Gear Ratio:	2.67:1

PROPELLER	
BRP™	
Material:	Aluminum
Diameter/Pitch:	14" X 11"
No. of Blades:	3
Part Number:	763301
MOUNTING HEIGHT	
Hole Position:	#2
Jack Plate:	N/A
AV Mounting:	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
850	1.9	0.10	18.8	540
1000	2.3	0.13	17.7	508
1500	3.2	0.20	16.3	470
2000	4.4	0.36	12.1	349
2500	5.4	0.63	8.6	247
3000	6.9	0.97	7.1	205
3500	7.7	1.34	5.7	165
4000	9.0	1.74	5.2	149
4500	11.1	2.23	5.0	143
5000	13.9	2.53	5.5	159
5500	15.7	3.11	5.1	145
5875	17.2	3.90	4.4	127
Range (Miles) Based On 90% Fuel Capacity				

TEST CONDITIONS	
Water Conditions:	Medium Chop
Wind Velocity:	15 MPH
Air Temperature:	75° F
Fuel Load:	1/2 Full
Weight:	2 Men, Fuel, Safety/Test Gear,

PERFORMANCE SUMMARY
Top Speed: 17.2 MPH
Best Fuel Efficiency: 5.7 MPG with a range of 165 Miles @ 7.7 MPH
Acceleration: 4.5 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2013 BRP US Inc. All rights reserved.

™ ® and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

