

EVINRUDE

E-TEC

PERFORMANCE REPORT

BULLETIN #: 1280

BOAT TYPE: Offshore

DATE OF TEST: 2/14/2018

ENGINE 1: C150AXH

Engine 2: C150AXC



BRP US, Inc.
10101 Science Drive
Sturtevant, WI 52177
www.evinrude.com



Dusky Marine
110 N. Bryan Road
Dania Beach, FL 33004
954-922-8890
<http://www.dusky.com>

2018 Dusky 278 Open Fisherman

BOAT	
2018 Dusky 278 Open Fisherman	
Material	Fiberglass
Length	27ft 8 in
Beam	8.5ft
Weight w/o Engine	4500 LBS
Maximum HP	450 HP
Fuel Capacity	100 Gallons
Transom Height	25"
Steering	I Dock

ENGINE	
Evinrude® E-TEC® G2™ Twin 150 HP	
Engine Type	66° V-6
Horsepower	150 H.O.
Displacement	2.7L
Induction	Direct Injection
Operating Range	RPM
Weight	LBS Dry Weight
Gear Ratio	0

PROPELLER	
BRP Rebel™	
Material	Stainless
Diameter/Pitch	15 3/8 X 18
No. of Blades	3
Part Number	763988
Prop Vent Hole	NA
MOUNTING HEIGHT	
Hole Position	#1
Jack Plate	No
AV Mounting	0

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
500	2.90	0.40	7.25	653
1000	5.40	1.15	4.70	423
1500	7.55	2.20	3.43	309
2000	9.20	4.10	2.24	202
2500	12.20	6.70	1.82	164
3000	19.10	8.65	2.21	199
3500	25.85	10.15	2.55	229
4000	30.80	12.45	2.47	223
4500	35.40	15.70	2.25	203
5000	39.30	18.55	2.12	191
5500	43.25	22.85	1.89	170
5800	45.35	25.80	1.76	158

TEST CONDITIONS	
Water Conditions	Light Chop
Wind Velocity	5 MPH
Air Temperature	80° F
Fuel Load	70 Gallons
Weight	Two Adults and Safety Gear

PERFORMANCE SUMMARY	
Top Speed	45.4 MPH
Best Fuel Efficiency	2.55 MPG For 229 Miles @ 25.85 MPH
Zero to 20 mph	4.2 seconds to plane

Fuel Data Range (Miles) Based On 90% Fuel Capacity



NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2015 BRP US Inc. All rights reserved.™ ® and the BPR logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

EVINRUDE

