



Bombardier Recreational Products Inc.  
10101 Science Drive  
Sturtevant, WI 52177  
[www.evinrude.com](http://www.evinrude.com)

*Hurricane*

Nautic Global Group  
4500 Middlebury St.  
Elkhart, IN 46516  
574-522-8381

[www.hurricaneboats.com](http://www.hurricaneboats.com)



### 2013 Hurricane SD 2400

| BOAT                   |            |
|------------------------|------------|
| 2013 Hurricane SD 2400 |            |
| Material:              | Fiberglass |
| Length:                | 24'        |
| Beam:                  | 102"       |
| Weight w/o Engine:     | 3735 L bs  |
| Maximum HP:            | 300 HP     |
| Fuel Capacity:         | 66 Gallons |
| Transom Height:        | 25" Shaft  |
| Steering:              | Hydraulic  |

| ENGINE                      |                    |
|-----------------------------|--------------------|
| 2013 Evinrude® 250 HP ETEC® |                    |
| Engine Type:                | 90° V6             |
| Horsepower:                 | 250 HP @ 5150 RPM  |
| Displacement:               | 3.3 Litre          |
| Induction:                  | ETEC DFI           |
| Operating Range:            | 4500-5800 RPM      |
| Weight:                     | 524 LBS Dry Weight |
| Gear Ratio:                 | 1.85:1             |

| PROPELLER       |                 |
|-----------------|-----------------|
| BRP Rebel       |                 |
| Material:       | Stainless Steel |
| Diameter/Pitch: | 15.5" X 17"     |
| No. of Blades:  | 3               |
| Part Number:    | 763986          |
| MOUNTING HEIGHT |                 |
| Hole Position:  | #2              |
| Jack Plate:     | N/A             |
| AV Mounting:    | N/A             |

| PERFORMANCE DATA                         |      |       |      |       |
|--|------|-------|------|-------|
| RPM                                      | MPH  | GPH   | MPG  | RANGE |
| 500                                      | 2.6  | 0.15  | 17.7 | 1060  |
| 1000                                     | 5.2  | 0.70  | 7.4  | 441   |
| 1500                                     | 6.9  | 1.70  | 4.1  | 244   |
| 2000                                     | 8.4  | 4.60  | 1.8  | 110   |
| 2500                                     | 11.6 | 6.15  | 1.9  | 113   |
| 3000                                     | 18.0 | 7.80  | 2.3  | 138   |
| 3500                                     | 27.1 | 8.95  | 3.0  | 182   |
| 4000                                     | 31.4 | 10.60 | 3.0  | 178   |
| 4500                                     | 35.6 | 11.95 | 3.0  | 179   |
| 5000                                     | 40.2 | 15.65 | 2.6  | 154   |
| 5500                                     | 44.2 | 18.55 | 2.4  | 143   |
| 5800                                     | 47.9 | 23.00 | 2.0  | 123   |
| Range (Miles) Based On 90% Fuel Capacity |      |       |      |       |

| TEST CONDITIONS   |                      |
|-------------------|----------------------|
| Water Conditions: | Calm                 |
| Wind Velocity:    | 5 MPH                |
| Air Temperature:  | 75° F                |
| Fuel Load:        | 60 Gallons           |
| Weight:           | 2 Men plus test gear |

| PERFORMANCE SUMMARY   |  |
|-----------------------|--|
| Top Speed:            | 47.9 MPH                                     |
| Best Fuel Efficiency: | 3.0 MPG with a range of 182 Miles @ 27.1 MPH |
| Acceleration:         | 3.3 seconds to plane                         |

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2009 BRP US Inc. All rights reserved.

™ ® and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

