

Bombardier Recreational Products Inc.
10101 Science Drive
Sturtevant, WI 53177
www.evinrude.com

Tahoe

Avalon & Tahoe Mfg
903 Michigan Avenue
Alma, MI 48801
1-989-463-2112

www.avalonpontoons.com



2014 Tahoe LT 2500

BOAT	
2014 Tahoe LT 2500	
Material:	Aluminum
Length:	25'
Beam:	8' 6"
Weight w/o Engine:	2450 Lbs
Maximum HP:	135 HP
Fuel Capacity:	45 Gallons
Transom Height:	20" Shaft
Steering:	Cable

ENGINE	
Evinrude® 115 HO ETEC®	
Engine Type:	60 Degree V4
Horsepower:	Factory Tuned
Displacement:	105.4 Cu In
Induction:	ETEC DFI
Operating Range:	5300-6000 RPM
Weight:	375 LBS Dry Weight
Gear Ratio:	2.00:1

PROPELLER	
BRP	
Material:	Aluminum
Diameter/Pitch:	14" X 11"
No. of Blades:	3
Part Number:	763301
MOUNTING HEIGHT	
Hole Position:	#2
Jack Plate:	N/A
AV Mounting:	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
600	1.9	0.18	10.4	420
1000	3.1	0.29	10.5	426
1500	4.9	0.60	8.1	328
2000	6.4	1.07	6.1	245
2500	8.5	1.75	4.9	198
3000	10.6	2.47	4.3	174
3500	14.7	4.34	3.4	137
4000	17.2	5.73	3.0	122
4500	19.3	6.93	2.8	113
5000	22.2	7.95	2.8	113
5500	24.4	9.28	2.6	107
5900	26.3	10.54	2.5	101
Range (Miles) Based On 90% Fuel Capacity				

TEST CONDITIONS	
Water Conditions:	Medium Chop
Wind Velocity:	10 MPH
Air Temperature:	85° F
Fuel Load:	1/4 Full
Weight:	2 Men, Fuel, Safety/Test Gear,

PERFORMANCE SUMMARY
Top Speed: 26.3 MPH
Best Fuel Efficiency: 4.3 MPG with a range of 174 Miles @ 10.6 MPH
Acceleration: 3.38 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2013 BRP US Inc. All rights reserved.

™ ® and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

